

# **Product datasheet** DULUX L 40 W/840 2G11

OSRAM DULUX L LUMILUX | CFLni, with 4-pin 2G11 base for ECG/CCG operation





April 29, 2024, 11:48:41 DULUX L 40 W/840 2G11

# Product datasheet

#### Technical data

### **Electrical data**

Nominal current	0.32 A A	
Photometrical data		
Light color (designation)	LUMILUX Cool White	
Rated LLMF at 4,000 h	0.9	
Rated LLMF at 6,000 h	0.88	
Rated LLMF at 8,000 h	0.85	
Rated LLMF at 12,000 h	0.84	
Rated LLMF at 16,000 h	0.81	
Rated LLMF at 20,000 h	0.8	
Luminous flux	3150 lm	

### **Dimensions & weight**

Overall length	538.00 mm
Tube diameter	17,5 mm
Length with base excl. base pins/connection	532 mm
Product weight	120.5 g

## Temperatures & operating conditions

Ambient temperature range	-5+40 °C
---------------------------	----------

### Lifespan

Service life	13000 h
Nominal lamp life time	12000 h

### Additional product data

# Product datasheet

Mercury content	3.5 mg	
Appropriate disposal acc. to WEEE	Yes	
Product remark	For ECG operation only	

## **Certificates & standards**

Energy efficiency class	G
Energy consumption	42.00 kWh/1000h

### **Country specific categorizations**

FSDH-40/840-/P/-2G11-43,9/533

## **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)					
Date of Declaration 18-04-2022					
Primary Article Identifier 4050300279909					
Declaration No. in SCIP database In work					

#### Equipment / Accessories

- Suitable for standard control gears and starters

- Suitable for operation on electronic and conventional control gear

SERIES CONNECTION WITH QUICKTRONIC

SERIES CONNECTION WITH QUICKTRONIC

SINGLE LAMP WITH QUICKTRONIC

#### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300279909	DULUX L 40 W/840 2G11	Shipping carton box 10 Pieces Folding carton box	572 mm x 136 mm x 109 mm	8.48 dm³	1663.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For more information on QUICKTRONIC electronic control gear go to

www.osram.com/QUICKTRONIC

For more information on the system guarantee and the terms and conditions of the guarantee visit https://

www.inventronics-light.com/multilevel-guarantees

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# Product datasheet

\_\_\_

OSRAM is distribution partner of LEDVANCE of LAMPS

# **OSRAM**

OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany

# DULUX L 40 W/840 2G11

OSRAM DULUX L LUMILUX | CFLni, with 4-pin 2G11 base for ECG/CCG operation

Product name	Product name ECG	EAN	Nominal current	Nominal wattage + Power loss	Power factor $\lambda$ [PIM]	Luminous flux at 35 °C
DULUX L 40 W/840 2G11	QTi 2x14/24/21/39 GII	4008321383396	0.37 A	86.00 W	0.98	3500 lm
	QTi 2x21/39 DIM	4050300870694	0.36 A	82.00 W	0.97	3500 lm
	QTP-DL 2x36-40	4008321117922	0.21 A	90.00 W	0.99	3650 lm
	QTP-M 1x26-42	4008321329134	0.19 A	43.00 W	0.98	3500 lm
	QTP-OPTIMAL 1x18-40	4008321873743	0.20 A	44.00 W	0.98	3500 lm
	QTP-OPTIMAL 2x18-40	4008321873767	0.37 A	88.00 W	0.99	3500 lm

Product name	Product name ECG	EAN	Number of lighting outlets
DULUX L 40 W/840 2G11	QTi 2x14/24/21/39 GII	4008321383396	2
	QTi 2x21/39 DIM	4050300870694	2
	QTP-DL 2x36-40	4008321117922	2
	QTP-M 1x26-42	4008321329134	1
	QTP-OPTIMAL 1x18-40	4008321873743	1
	QTP-OPTIMAL 2x18-40	4008321873767	2