

Product family datasheet

LUMILUX T5 HO

Tubular fluorescent lamps 16 mm, high output, with G5 base



Product family datasheet

Technical data

	Electrical data	Photometrical data	Dimensions & weight			Additional product data	
Product description	Nominal current	Light color (designation)	Tube diameter	Product weight	Overall length	Product remark	Predecessor EAN
HO 24 W/840 ¹⁾	0.3 A A	LUMILUX Cool White	16 mm	44.26 g	563.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300453477
HO 39 W/840 ¹⁾	0.33 A A	LUMILUX Cool White	16 mm	70.92 g	863.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300453538
HO 49 W/830 ¹⁾	0.26 A A	LUMILUX Warm White	16 mm	116.45 g	1463.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	

Product family datasheet

	Electrical data	Photometrical data	Dimensions & weight			Additional product data	
Product description	Nominal current	Light color (designation)	Tube diameter	Product weight	Overall length	Product remark	Predecessor EAN
HO 49 W/840 ¹⁾	0.26 A A	LUMILUX Cool White	16 mm	116.45 g	1463.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300657134
HO 54 W/830 ¹⁾	0.46 A A	LUMILUX Warm White	16 mm	88.02 g	1163.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300453415
HO 54 W/840 ¹⁾	0.46 A A	LUMILUX Cool White	16 mm	88.02 g	1163.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300453392
HO 80 W/840 ¹⁾	0.53 A A	LUMILUX Cool White	16 mm	116.45 g	1463.20 mm	Suitable for ECG operation only Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C	4050300515151

Product family datasheet

		Certificates & standards		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Successor EAN	Energy efficiency class	Energy consumption	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
HO 24 W/840 ¹⁾	4050300591643	G	24.00 kWh/1000h	18-04-2022	4050300453477 4050300591643	In work
HO 39 W/840 ¹⁾	4050300591704	G	39.00 kWh/1000h	18-04-2022	4050300453538 4050300591704	In work
HO 49 W/830 ¹⁾		F	50.00 kWh/1000h	18-04-2022	4050300657158	In work
HO 49 W/840 ¹⁾	4050300796710	F	50.00 kWh/1000h	18-04-2022	4050300796710 4050300657134	In work
HO 54 W/830 ¹⁾	4050300591605	F	54.00 kWh/1000h	18-04-2022	4050300453415	In work
HO 54 W/840 ¹⁾	4050300591582	F	54.00 kWh/1000h	18-04-2022	4050300453392 4050300591582	In work
HO 80 W/840 ¹⁾	4050300591841	G	81.00 kWh/1000h	18-04-2022	4050300591841 4050300515151	In work

¹⁾ Suitable for ECG operation only/Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C

Product family datasheet



HO 24 W/840, HO 39 W/840, HO 49 W/830, HO 49 W/840, HO 54 W/830, HO 54 W/840, HO 80 W/840

HO 24 W/840, HO 39 W/840, HO 49 W/840, HO 54 W/840, HO 80 W/840

HO 49 W/830, HO 54 W/830

System guarantee

OSRAM System+ Guarantee in combination with OSRAM ECGs

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300453477	HO 24 W/840	Shipping carton box 40	600 mm x 194 mm x 88 mm	10.24 dm ³	2486.00 g
4050300591643	HO 24 W/840	Shipping carton box 20	582 mm x 104 mm x 83 mm	5.02 dm ³	1321.00 g
4050300591704	HO 39 W/840	Shipping carton box 20	882 mm x 104 mm x 83 mm	7.61 dm ³	1950.00 g
4050300657158	HO 49 W/830	Shipping carton box 40	1498 mm x 161 mm x 103 mm	24.84 dm ³	6525.00 g
4050300657134	HO 49 W/840	Shipping carton box 40	1498 mm x 161 mm x 103 mm	24.84 dm ³	6525.00 g
4050300796710	HO 49 W/840	Shipping carton box 20	1511 mm x 104 mm x 88 mm	13.83 dm ³	3498.00 g
4050300453415	HO 54 W/830	Shipping carton box 40	1200 mm x 194 mm x 83 mm	19.32 dm ³	4813.00 g
4050300453392	HO 54 W/840	Shipping carton box 40	1198 mm x 198 mm x 95 mm	22.53 dm ³	4720.00 g
4050300591582	HO 54 W/840	Shipping carton box 20	1187 mm x 110 mm x 90 mm	11.75 dm ³	2710.00 g

Product family datasheet

Logistical Data

4050300515151	HO 80 W/840	Shipping carton box 40	1500 mm x 194 mm x 88 mm	25.61 dm ³	6340.00 g
4050300591841	HO 80 W/840	Shipping carton box 20	1487 mm x 110 mm x 90 mm	14.72 dm ³	3690.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit <https://www.inventronics-light.com/multilevel-guarantees>

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany