

Product datasheet L 15 W/827

LUMILUX T8 | Tubular fluorescent lamps 26 mm, with G13 bases







Technical data

Electrical data

Photometrical data

Light color (designation)	LUMILUX INTERNA
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.94
Rated LLMF at 6,000 h	0.93
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.9
Rated LLMF at 20,000 h	0.96
Luminous flux	950 lm

Dimensions & weight



Tube diameter	26 mm
Length with base excl. base pins/connection	438,00 mm
Product weight	60.00 g
Overall length	451.60 mm

Lifespan

Service life	16000 h
--------------	---------

Additional product data

Mercury content	3.0 mg
Appropriate disposal acc. to WEEE	Yes

Certificates & standards

Energy efficiency class	G		
Energy consumption	15.00 kWh/1000h		

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	19-01-2022	
Primary Article Identifier	4050300446042	
Declaration No. in SCIP database	In work	

Light Distribution

FL_827

System guarantee

OSRAM System+ Guarantee in combination with OSRAM ECGs

DUO CIRCUIT

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300446042	L 15 W/827	Shipping carton box 25 Pieces Sleeves	508 mm x 155 mm x 147 mm	11.57 dm³	2594.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system quarantee and the terms and conditions of the quarantee visit https://

www.inventronics-light.com/multilevel-guarantees

For more information on QUICKTRONIC electronic control gear go to

www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany

L 15 W/827

LUMILUX T8 | Tubular fluorescent lamps 26 mm, with G13 bases