

Product datasheet L 30 W/840

LUMILUX T8 | Tubular fluorescent lamps 26 mm, with G13 bases







Technical data

Electrical data

Photometrical data

Light color (designation)	LUMILUX Cool White
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.94
Rated LLMF at 6,000 h	0.93
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.9
Rated LLMF at 20,000 h	0.96
Luminous flux	2400 lm

Dimensions & weight



Tube diameter	26 mm
Length with base excl. base pins/connection	895,00 mm
Product weight	120.00 g
Overall length	908.80 mm

Lifespan

Service life	16000 h
Jei vice tile	1000011

Additional product data

Mercury content	3.0 mg
Appropriate disposal acc. to WEEE	Yes

Certificates & standards

Energy efficiency class	G	
Energy consumption	32.00 kWh/1000h	

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	19-01-2022	
Primary Article Identifier	4050300518039	
Declaration No. in SCIP database	In work	

Light Distribution

System guarantee

FL_840

OSRAM System+ Guarantee in combination with OSRAM ECGs

DUO CIRCUIT

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300518039	L 30 W/840	Shipping carton box 25 Pieces Sleeves	142 mm x 145 mm x 937 mm	19.29 dm³	3910.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system quarantee and the terms and conditions of the quarantee visit https://

www.inventronics-light.com/multilevel-guarantees

For more information on QUICKTRONIC electronic control gear go to

www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany

L 30 W/840

LUMILUX T8 | Tubular fluorescent lamps 26 mm, with G13 bases