

# **QUICKTRONIC FIT 8**

ECG for FL 26 mm



#### Product family features

Supply voltage: 220...240 VLine voltage: 198...264 VLine frequency: 50 Hz | 60 Hz

- Lamp start with optimum filament preheating

- Energy Efficiency Index EEI: A2

– Automatic shutdown of defective lamps and at end of life

(EoL T.2)

Lamp operation: to EN 60929Safety: to EN 61347-2-3

## Product family benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

#### Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting
- Suitable for luminaires of protection class I

## Product family datasheet

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Additional product information

- In order to achieve good radio interference suppression:1. Keep the cable between ECG and lamp as short as possible.2. The single lamp wires must be routed as close as possible to each other, whereas the lines of the different lamp ends must be routed separately.

#### Sales and Technical Support

Sales and Technical Support www.osram.com

#### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.