

64672 500 W 230 V

Halogen lamps, medium/high voltage, single-ended



Areas of application

- Professional film and TV work

Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V

- Color temperature: 2,900 K | 3,000 K (with longer lifespan)

- Color temperature: 3,200 K (for professional film and TV work)

- Color temperature: 3,400 K (for maximum luminous efficacy)







Product datasheet

Technical data

Product information


Electrical data

| Nominal wattage | 50000 W | |
|-------------------------------|-----------------|--|
| Nominal voltage | 230 V | |
| On-mode power | 525.00 W | |
| Energy consumption in on-mode | 525.0 kWh/1000h | |

Photometrical data

| Color temperature | 2900 K |
|------------------------------------|---------|
| Color rendering index Ra | 100 |
| Φuse value refers to luminous flux | 360 |
| Correlated color temperature CCT | 2883 K |
| Useful luminous flux (Φuse) | 7905 lm |
| Chromaticity coordinate x | 0.446 |
| Chromaticity coordinate y | 0.407 |

Dimensions & weight



| Diameter | 220 mm |
|-------------------|---------------|
| Length | 899 mm |
| Illuminated field | 12.0*11.0 mm² |
| Filament diameter | 11.0 mm |

Lifespan

| Lifespan | 2000 h |
|----------|--------|

Product datasheet

Additional product data

| Base (standard designation) | GY9.5 |
|-----------------------------|-------|
| Lighting technology used | HL |

Capabilities

| Burning position | Any |
|------------------|-----|

Certificates & standards

| Energy efficiency class | G |
|-------------------------|---|
|-------------------------|---|

Country specific categorizations

| ANSI code | Other |
|-----------------|----------------|
| Order reference | 64672 M40 500W |

Logistical data

| EAN 10 of contained light source | 4008321098559 |
|----------------------------------|---------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
|---|------------------------------------|--|--|
| Date of Declaration 22-04-2024 | | | |
| Primary Article Identifier | 4008321098559 | | |
| Candidate List Substance 1 | No declarable substances contained | | |
| Declaration No. in SCIP database No declarable substances contained | | | |

Country specific information

| Product code | METEL code | SEG-No. | STK-Number | UK Org |
|---------------|------------|---------|------------|--------|
| 4008321098559 | OSRH64672 | - | - | - |
| 4008321098559 | OSRH64672 | - | - | - |

Product datasheet

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4008321098559 | 64672 500 W 230 V | Folding carton box 1 | 42 mm x 42 mm x 111 mm | 0.20 dm ³ | 23.00 g |
| 4008321098566 | 64672 500 W 230 V | Shipping carton box 12 | 180 mm x 127 mm x 140 mm | 3.20 dm ³ | 544.33 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further information on pinch technology, please refer to the following brochure:

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

[&]quot;A whole lotta shakin' goin' on!" New halogen lamps with quartz pinch technology. (122 W 100 DE 08/05)