

# XBO 75 W/2 OFR

XBO Xenon short-arc lamps without reflector | Xenon short-arc lamps without reflector



### Product family benefits

- Very high luminance (point light source)
- Continual color quality, irrespective of lamp type and lamp wattage
- Constant light color throughout the life of the lamp
- Long lamp life

#### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index: R<sub>a</sub> >
- Continuous spectrum in the visible range
- High arc stability
- Hot restart capability
- Dimmable
- Instant light on starting



April 25, 2024, 01:42:07 XBO 75 W/2 OFR

### Technical data

### **Electrical data**


Lamp wattage	64 W	
Lamp current	4959 A	
Type of current	DC	

### Photometrical data

Nominal luminous flux	1000 lm		
Luminous intensity	100 cd <sup>1)</sup>		
Luminance	40000 cd/cm <sup>2</sup> <sup>1)</sup>		

1) Typical initial photometric value

### **Dimensions & weight**



Length	900 mm	
Length with base excl. base pins/connection	82.00 mm	
Product weight	1100 g	

### Lifespan

Lifespan	400 h
Enespan	400 11

### Additional product data

Base anode (standard designation)	SFa9-2
Base cathode (standard designation)	SFa7.5-2

# Capabilities

Cooling	Convection		
Burning position	s100 <sup>1)</sup>		
Application	Other		

 $^{1)}$  If vertical, then anode on top; up to  $10^\circ$  below horizontal, cathode on top

### **Environmental information**

# Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	05-03-2024		
Primary Article Identifier	4050300508825		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	536f5044-6629-4551-b556-81347c0c9dfe		

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300508825	OSRXBO7520FR	-	-	-
4050300508825	OSRXBO752OFR	-	-	-

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300508825	XBO 75 W/2 OFR	Folding carton box 1	165 mm x 95 mm x 48 mm	0.75 dm³	91.00 g
4050300508832	XBO 75 W/2 OFR	Shipping carton box 10	235 mm x 225 mm x 210 mm	11.10 dm³	1138.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

Further technical information on XBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.