

## HBO 2001 W/NIL

HBO-IC Microlithography lamps for Nikon i-line systems | Microlithography lamps for Nikon i-line systems




Technical data

Electrical data

Nominal voltage	260 V
Nominal current	67 A
Type of current	DC
Rated wattage	175000 W
Nominal wattage	2000.00 W

Dimensions & weight



Diameter	520 mm
Length	2510 mm
Mounting length	251.0 mm
Length with base excl. base pins/connection	219.00 mm
Light center length (LCL)	122.25 mm <sup>1)</sup>
Electrode gap cold	4.5 mm

<sup>1)</sup> Distance from end of base to tip of anode or cathode (cold)

Additional product data

Product remark	Also available as Super Longlife version with 2,250 h lifespan: HBO 2001 W/NIEL (4050300538211)
----------------	---

Capabilities

Burning position	Other <sup>1)</sup>
------------------	---------------------

<sup>1)</sup> Anode underneath

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	05-03-2024

Product datasheet

Primary Article Identifier	4050300461489
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	51d17212-f48f-4e56-91b0-487db4ddc57b

# Product datasheet

## Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300461489	HBO 2001 W/NIL	Sliding sleeve 1	385 mm x 195 mm x 160 mm	12.01 dm <sup>3</sup>	1315.00 g
4050300461496	HBO 2001 W/NIL	Shipping carton box 6	510 mm x 420 mm x 420 mm	89.96 dm <sup>3</sup>	8804.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.