# **OSRAM**

## **ONYX COPILOT**

Flexible LED reading light



20 lm Pleasantly warm and glare-free light

### 37 cm

370 mm neck length powered via cigarette lighter or with a plastic base for fixed connection

## 12 V + 24 V

The stylish light is suitable for both passenger cars (12 volt) and trucks (24 volt)



## Precisely illuminating vehicle interiors

With its elegant and dynamic design, the ONYX COPILOT LED reading light achieves seamless integration into vehicle interiors. With its high flexibility, the reading light has a wide range of options for illuminating specific areas of the vehicle interior. The neck of the light is made of matt black silicon rubber and can be individually adjusted. The LED lifetime of ONYX COPILOT is extremely long: up to 20,000 hours! The Luminaire can be switched on/off and remain connected permanently. OSRAM provides a 2 year guarantee for this stylish light.

## Product family datasheet

## Technical data

|                     | Product information       |   |                   | Electrical data          |                    | Photo        | Photometrical data                      |                  |
|---------------------|---------------------------|---|-------------------|--------------------------|--------------------|--------------|---|------------------|
| Product description | Order reference           | Application (Category and Product specific) |                   | Nominal<br>wattage       | Nominal<br>voltage | Light<br>LED | color                                   | Luminous<br>flux |
| ONYX COPILOT M+7    | ONYX M+7                  | Flexible LED<br>light                       | reading           | 0.50 W                   | 12/24 V            | Warm         | white                                   | 20 lm            |
| ONYX COPILOT        | ONYXCOPI<br>LOT L+7       | Flexible LED<br>light                       | reading           | 0.5 W                    |                    |              |   | 18 lm            |
|                     |                           | Dimensions &                                | weight            |                          |                    |              | Colors                                  | & materials      |
| Product description | Color<br>temper-<br>ature | Length                                      | Product<br>weight | Height                   | Width              |              | Base co                                 | olor             |
| ONYX COPILOT M+7    | 3200 K                    | 0.0 mm                                      | 84.00 g           |                          |                    |              | Black                                   |                  |
| ONYX COPILOT        | 3000 K                    | 460.0 mm                                    | 72.00 g           | 9.0 mn                   | n 25.0 r           | nm           | Black                                   |                  |
|                     | Lifespan                  | Capabilities                                | Certific          | Certificates & standards |                    |              | informa<br>Informa<br>accordi<br>EU Reg |                  |
| Product description | Guarantee                 | Technology                                  | Standa            | rds                      | Type o             |              | Date of                                 | f Declaration    |
| ONYX COPILOT M+7    | 3 years                   | LED   | CE                |                          | IP20               |              | 21-08-                                  | 2023             |
| ONYX COPILOT        |                           | LED   | CE                |                          | IP20               |              | 06-03-                                  | 2024             |

| Product description | Primary Article<br>Identifier | Declaration No. in SCIP database             | Candidate List<br>Substance 1 | CAS No. of substance<br>1 |
|---------------------|-------------------------------|--|-------------------------------|---------------------------|
| ONYX COPILOT M+7    | 4062172339377                 | In work                                      |                               |                           |
| ONYX COPILOT        | 4052899414938                 | abeee974-0574-<br>456e-82ec-<br>afd9be936f89 | Lead                          | 7439-92-1                 |

| Product description | Safe Use Instruction  |  |  |  |  |
|---------------------|-----------------------|--|--|--|--|
| ONYX COPILOT M+7    |                       |  |  |  |  |
| ONYX COPILOT        | The identification of |  |  |  |  |
|                     | the Candidate List    |  |  |  |  |
|                     | substance is          |  |  |  |  |
|                     | sufficient to allow   |  |  |  |  |
|                     | safe use of the       |  |  |  |  |
|                     | article.              |  |  |  |  |

## Product family datasheet

## Equipment / Accessories

- Matching mating plug AMP 626064-0
- Matching plugs: AMP 1217281-2, 63241-3, 62572-6 or 1217321-2

#### **Download Data**

File



User instruction 347902\_UI LED ONYX COPILOT L



User instruction
LED ONYX COPILOT L

## **References / Links**

Guarantee terms are available at www.osram.com/am-guarantee

## **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.