

Product family datasheet

## LEDiving BASIC P21/5W



## Product family datasheet

### Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
LEDriving BASIC $\pm$ P21/5W	1.44 W	12 V	1 W	13.5 V	85/25 lm



Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDriving BASIC $\pm$ P21/5W	$\pm 20\%$	20.0 mm	2000 hr	2000 hr	4052899463295   4052899414518   4052899414495

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC $\pm$ P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9bf3b981-7442-439c-a86d-e513fc794734   fe6d71fd-c80e-400d-8cc2-14ed29394294   1d480114-7d33-4144-80cc-0d5f7210d25e

## Product family datasheet

---

### Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

