

Product family datasheet

## LEDiving BASIC R5W



## Product family datasheet

### Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
LEDriving BASIC $\pm$ R5W	0.96 W	12 V	0 W	13.5 V	55 lm



Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDriving BASIC $\pm$ R5W	$\pm$ 20 %	19.0 mm	2000 hr	2000 hr	4052899463332   4052899414556   4052899463127   4052899414532

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC $\pm$ R5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	12c61241-8e84-49d2-aad6-61ee9185fc4c   a74edd59-fe84-466f-9e9c-d76036657cbc   4deab8c0-c089-4d6a-90f4-3738f5af799e   e8c7bd92-d6cb-4cf2-9e8f-8360bae74918   eb08c6c5-5573-4254-af17-5f6a4f492b5f

## Product family datasheet

---

### Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

