OSRAM

LEDriving BASIC R10W



Product family datasheet

Technical data

19.0 mm

	Product information		General Product Information		Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)		Global order reference		Nominal voltage
LEDriving BASIC ≜ R10W	Mainly used for signal/indicator applications	Off-road ≙ R10W	5108CV	V	1.44 W	12 V
			Photometric Data			Physical Attributes & Dimensions
Product description	Nominal wattage	Test voltage	Nominal flux		Luminous flux tolerance	Diameter
LEDriving BASIC = R10W	1 W	13.5 V	85 lm		±20 %	19.0 mm
		Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Diameter		Lifespan Tc	Technology	Primary art	icle

2000 hr

2000 hr

LED

4052899414570 | 4052899463141 | 4052899414594 | 4052899463356

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC ≜ R10W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	1068a570-b34f- 446b-84ce- 0f878db5b787 2115fbba-97ea- 4065-9557- f01077d71065 3d88abbd-dd35- 4bb0-bea6- 4442158e669d b202dc8f-679a- 4862-8048- 9e2fbcf9ed99 dcfc1ce0-153b-4d18- a86d-faf190a5a112

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

