

Product family datasheet

LEDiving BASIC R10W



Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
LEDriving BASIC \pm R10W	1.44 W	12 V	1 W	13.5 V	85 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDriving BASIC \pm R10W	± 20 %	19.0 mm	2000 hr	2000 hr	4052899414570 4052899463141 4052899414594 4052899463356

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC \pm R10W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	1068a570-b34f-446b-84ce-0f878db5b787 2115fbba-97ea-4065-9557-f01077d71065 3d88abbd-dd35-4bb0-bea6-4442158e669d b202dc8f-679a-4862-8048-9e2fbcf9ed99 dcfc1ce0-153b-4d18-a86d-faf190a5a112

Product family datasheet

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

