

Product family datasheet

## LEDDriving BASIC P21/5W



## Product family datasheet

### Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux
LEDiving BASIC $\pm$ P21/5W	1.44 W	12 V	1 W	$\pm 20 \%$	13.5 V	85/25 lm

Product description	Physical Attributes & Dimensions			Lifetime Data
	Lamp base	Length	Diameter	Lifespan B3
LEDiving BASIC $\pm$ P21/5W	BAY15d	38.2 mm	20.0 mm	2000 hr



Product description	Lifespan Tc	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
		Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDiving BASIC $\pm$ P21/5W	2000 hr	4052899463295   4052899414518   4052899414495	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDiving BASIC $\pm$ P21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9bf3b981-7442-439c-a86d-e513fc794734   fe6d71fd-c80e-400d-8cc2-14ed29394294   1d480114-7d33-4144-80cc-0d5f7210d25e

## Product family datasheet

---

### Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

