

Product family datasheet PARATHOM Retrofit CLASSIC P DIM

Dimmable LED lamps, classic bulb shape



 Perfect for decorative installations Domestic applications General illumination Outdoor use in outdoor luminaires only (minimum IP65)

 Design, dimensions, luminous flux comparable to an incandescent lamp Very low energy consumption Robust against vibrations Lamps with innovative LED "filament" technology Instant 100 % light, no warm-up time Can be easily fitted instead of ordinary light bulbs




Technical data

	Electrical data			Photometrical data	Light technical data	Dimensions & weight	
Product description	Operating frequency	Claimed equiv. conventional lamp power	Nominal current	Light color (designation)	Beam angle	Overall length	Product weight
P RF CLAS P DIM 280 W/827 E27 ¹⁾	5060 Hz	25 W	13 mA	Warm White	320 °	77.00 mm	18.00 g
	Temperatures & operating conditions	Lifespan	Additional product dat	duct data Certificates & standards		ls	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Ambient temperature range	Lumen maintenance at end of service life	Mercury-free	Product remark	Energy efficiency class	Energy consumption	Date of Declaration
P RF CLAS P DIM 280 W/827 E27 ¹⁾	-20+40 °C	0.7	Yes	Dimmable (with many common dimmers, see also www.ledvance.com/d im)	F	3.00 kWh/1000h	18-04-2022

Product description	Primary Article Identifier	Declaration No. in SCIP database
P RF CLAS P DIM 280 W/827 E27 $^{1)}$	4058075590816	In work

1) All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Product family datasheet



P RF CLAS P DIM 280 W/827 E27

Application advice

For more detailed application information and graphics please see product datasheet.

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075590816	P RF CLAS P DIM 280 W/827 E27	Shipping carton box 10	240 mm x 101 mm x 108 mm	2.62 dm ³	338.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany