

PL-LIN-Z6 4000-940 560X20-LV

PrevaLED Linear G6 CRI90 | Linear Light Engines



Product family features

- Module efficacy: up to 173 lm/W
- Available with luminous flux: 245 lm on 62 mm, 275 lm on 70 mm
- Available with luminous flux: 1,100 lm or 2,000 lm on 280 mm
- Available with luminous flux: 2,200 lm or 4,000 lm on 560 mm
- Color rendering index: > 90
- High initial color consistency: ≤ 3 SDCM
- Average lifetime (L80 B50): > 70,000 h (temperature at $T_c = 50^\circ\text{C}$)
- CE marked, ENEC certified; UL listed

Product family benefits

- Slim luminaire design by small and flexible form factor
- High homogeneity thanks to small LED pitch
- High voltage (HV) optimized for non-isolated, low voltage (LV) optimized for SELV operation
- Adjustable luminous flux, efficacy and lifetime
- Direct the light where it's needed while using PrevaLED Linear Optics

Areas of application

- Office
- Industry



Technical data

Electrical data

Nominal voltage	432 V
Nominal current	06 A
Type of current	DC
On-mode power	26.60 W
Energy consumption in on-mode	26.6 kWh/1000h

Photometrical data

Luminous efficacy	158 lm/W
Color rendering index Ra	90
Correlated color temperature CCT	4000 K
Colour consistency (McAdam ellipses)	3
Useful luminous flux (Φ_{use})	3807 lm


Light technical data

Starting time	< 01 s
Warm-up time (60 %)	< 200 s

LED module information

Number of LEDs per module	96
---------------------------	----

Dimensions & weight



Product weight	4000 g
Height	5.0 mm
Length	560.0 mm
Width	20.0 mm

Temperatures & operating conditions

Performance temp. acc. to IEC 62717	50 °C
Temperature range in operation at Tc point	-20...75 °C
Maximum temperature at tc test point	75 °C
Temperature range at storage	-30...85 °C
Ambient temperature range	-20...+75 °C

Lifespan

Number of switching cycles	100000
Lumen maintenance factor LMF	96
L70B50 lifetime	100000 h

Additional product data

Lighting technology used	LED
Predecessor EAN	4052899985476

Certificates & standards

Standards	CE/ENEC/VDE
Type of protection	IP20
Energy efficiency class	E

Logistical data


Commodity code	85414100000
----------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4052899606869
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained



484525_5 Year Osram Guarante
(GB)



PL LIN G5 G6 Mounting Guidance 251021

Additional product information

- When parallel wiring, tolerance-related differences in output are possible and may cause deviations in brightness.

Download Data

File	
	Certificates PL ENEC 40031612 250723
	Declarations of conformity PL LIN Z6 CE 3812352 090823
	Declarations of conformity EU Declaration of conformity PL-LIN-Z4 family
	Declarations of conformity Declaraton of conformity PL-LIN-Z4
	CAD data 3-dim PL LIN Z5 Z6 4000 560x20 LV CADPDF 240220

Product datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899606869	PL-LIN-Z6 4000-940 560X20-LV	Shipping carton box 60	592 mm x 252 mm x 100 mm	14.92 dm ³	2838.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.