OSRAM

LEDriving FL PSX24W





Superior brightness

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



Ultra compact LED replacement for conventional PSX24W fog lamps as socket solution

Easy installation with optimized compatibility

Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps with state-of-the-art LED technology. The color temperature of 6,000K provides for a stylish cool white look and improved visibility.

Product family datasheet

Technical data

	Product inform	Product information				Electrical data			
Product description	reference	Product type (off- road vs. on-road)	Application (Category and Product specific)		Nominal voltage	Nominal wattage	Test voltage		
LEDriving FL ≙ PSX24W		Off-road ≙ PSX24W	Mainly used for headlight/ fog light applications		12.0 V	8.20 W	13.2 V		
	Photometrical data		Dimensions & weight	Lifespan		Capabilities			
Product description	Luminous flux tolerance	Luminous flux	Diameter	Lifespan B3	Lifespan Tc	Technology			
LEDriving FL ≙ PSX24W	±20 %	730 lm	18.0 mm	2500 h	5000 h	LED			
		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)							
Product description	Date of Declara			,		eclaration No. in CIP database			
LEDriving FL ≜ PSX24W	07-03-2024	40 40 40		62172058360 In 62172058346 59089376878 59089349520 62172401852					

Product family datasheet

Download Data

File



Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

LEDriving CANBUS CONTROL UNIT (LEDCBCTRL102) avoids error messages on the board computer when using LED fog lights within 21 W applications

Refer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.









