

# Lightbar SX180-SP

Improved safety on-road and off-road with the full force of LEDs



## Compact housing design

Compact mounting dimensions enables a wide range of possible applications



## Lighting distance up to 190 meters

Increased far field illumination



## Spot Beam

Highly concentrated light beam



### Durable and robust LED auxiliary light with certified approval for use on roads

Bright light is particularly critical on unlit streets and dirt roads. It lets drivers identify obstacles on the road far in advance. With its six high-performance LEDs, the LEDriving Lightbar SX180-SP automotive auxiliary light gives drivers better visibility and improved safety on the road. And the LED auxiliary light also impresses at shorter distances. With an illuminance of one lux and a beam angle of eight degrees, the beam of light can reach up to 190 meters. That's sufficient enough to identify obstacles on the road far in advance. The sophisticated reflector design of the LED search light provides very high optical efficiency with uniform light distribution and reduced glare. Reduced glare is especially relevant for oncoming traffic and counts as another important aspect of road safety. Beyond its light output, the LED high beam enhances the off-road style of the vehicle. Because the LED auxiliary light with certified approval is intended for roads, its use is not limited to off-road terrain. Various mounting options & durability It goes without saying that the LED auxiliary light has to withstand quite a bit when used almost daily. Its hard-wearing polycarbonate lens allows it to meet even the toughest demands while extending the lifespan of the auxiliary light for automobiles. An integrated driver and thermal management system prevents possible damage from overheating. Over and under voltage protection automatically breaks the circuit when power exceeds the predetermined current for a specified amount of time. Even major temperature fluctuations aren't a problem for the LEDriving Lightbar SX180-SP LED auxiliary lights. They work whether the air temperature is a very cold -30 or a hot 60 degrees Celsius. This is a very helpful feature, particularly during off-road tours. Its compact mounting dimensions allow the LED working light to be mounted in a variety of ways. The LED auxiliary light can be easily installed even on the front end of 4x4 and off-road vehicles as well as utility and industrial vehicles.

Technical data

Product information

|   |                                  |
|---|----------------------------------|
| Order reference                             | LEDDL105-SP                      |
| Application (Category and Product specific) | Additional high beam application |


Electrical data

|                 |         |
|-----------------|---------|
| Nominal voltage | 12/24 V |
| Nominal wattage | 15 W    |
| Test voltage    | 13.5 V  |

Photometrical data

|                       |         |
|-----------------------|---------|
| Luminous flux         | 1300 lm |
| Color temperature     | 6000 K  |
| Light distance at 1lx | 190 m   |

Dimensions & weight




|                |          |
|----------------|----------|
| Product weight | 440.00 g |
| Length         | 182.0 mm |
| Width          | 62.0 mm  |
| Height         | 38.0 mm  |

Lifespan

|             |         |
|-------------|---------|
| Lifespan Tc | 5000 h  |
| Guarantee   | 5 years |

Additional product data



Luminous intensity distribution

|                   |              |
|-------------------|--------------|
| Connector to lamp | DT Connector |
|-------------------|--------------|

Capabilities

|            |     |
|------------|-----|
| Technology | LED |
|------------|-----|

Certificates & standards

|                           |               |
|---------------------------|---------------|
| Standards                 | ECE R10, R112 |
| Approval marks – approval | E4 approval   |
| Type of protection        | IP69K         |

Country specific categorizations

|                 |             |
|-----------------|-------------|
| Order reference | LEDDL105-SP |
|-----------------|-------------|

Logistical data

|                |             |
|----------------|-------------|
| Commodity code | 85122000900 |
|----------------|-------------|

Environmental information

|   |
|---|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|---|

Product datasheet

|                                  |  |
|----------------------------------|--|
| Date of Declaration              | 28-02-2024   |
| Primary Article Identifier       | 4052899595415  |
| Candidate List Substance 1       | Lead   |
| CAS No. of substance 1           | 7439-92-1  |
| Safe Use Instruction             | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database | a1bdcbc4-aa38-44ed-b994-4a48e9654415   |






Product Info Graphics

Logistical Data









| Product code  | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume                | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899595415 | Lightbar SX180-SP   | Folding carton box<br>1      | 283 mm x 137 mm x 89 mm              | 3.45 dm <sup>3</sup>  | 626.00 g     |
| 4052899595422 | Lightbar SX180-SP   | Shipping carton box<br>8     | 371 mm x 304 mm x 307 mm             | 34.62 dm <sup>3</sup> | 5523.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File  |  |
|---|--|
|  | User instruction<br>LEDriving  |
|  | Movie application<br>OSRAM Quality Testing LEDriving working and driving lights (EN) |
|  | Movie application<br>OSRAM LEDdriving and working lights Imagefilm (EN)              |

Product datasheet

|   |  |
|---|--|
|  | Movie application<br>LEDriving Driving and Working Lights Reference Video (EN)                             |
|  | Movie application<br>Working and Driving Lights Amarok Winter  |
|  | Movie application<br>LEDriving driving & working lights in application (EN)                                |
|  | Video<br>Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)                   |
|  | Video<br>OSRAM LEDriving driving and working lights: The night doesn't stand a chance                      |
|  | Video<br>OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN) |
|  | Video<br>Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads  |
|  | 360 Degree Image<br>LEDriving Lightbar LEDDL105-SP   |

Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairs

Precise terms and conditions at: [www.osram.com/guarantee](http://www.osram.com/guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM