

# TYREinflate 450



## Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 3.5 minutes\*\*



## Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



## LED Light

Easy to operate even in darkness and in low light conditions



## Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 450 can inflate a tyre from flat in 3.5 minutes\*\*. Comes with auto stop feature to accurately get the desired pressure for your tyre. Includes a backlit digital display and white LED light for optimal illumination in darkness.

The Tyreinflate 450's flat, solid design makes the unit stable whilst in use, as well as the wind up cable eliminating any messy wires and helping you get back on the road faster.

Comes complete with three piece adaptor kit for bicycle tyres, balls and other inflatables.

\*\*based on inflating a 13" tyre from flat to 2.41 BAR










Product family datasheet

Technical data

| Product description | General Product Information   | Electrical Data        | Physical Attributes & Dimensions   |                                      |
|---------------------|---|------------------------|--|--------------------------------------|
|                     | Global order reference  | Nominal voltage        | Height   | Width                                |
| TYRE inflate 450    | OTI450  | 11.1 V                 | 180.0 mm   | 88.0 mm                              |
| Product description | Length  | Operating Conditions   | Additional product data  | Capabilities                         |
|                     |   | Noise Level (dB)       | Display Type   | Fuse                                 |
| TYRE inflate 450    | 197.0 mm  | 90 dB                  | Digital  | 10 A                                 |
| Product description | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                        |  |                                      |
|                     | Candidate list substance 1  | CAS No. of substance 1 | Safe use instruction   | Declaration no. in SCIP database     |
| TYRE inflate 450    | Lead  | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | dda41c6e-d521-4522-a227-e170d9cf4d66 |

# Product family datasheet

## Download Data

| File   |   |
|--|---|
|   | User instruction<br>TYREinflate 450   |
|   | Movie application<br>TyreInflate How to Video (RU)  |
|   | Product movie<br>TyreInflate 450 Product Video (EN)   |
|   | Product movie<br>TyreInflate 450 Product Video (RU)   |
|   | Product movie<br>TyreInflate How to Video (EN)  |
|   | Product movie<br>TyreInflate How to Video (IT)  |
|   | Product movie<br>TyreInflate 450 Product Video (ITA)  |
|   | Video<br>OSRAM TYREinflate 450: Rapid tyre inflator with wind-up cable, LED light and digital display |
|  | Video<br>OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily                         |

### Safety advice

Product won't exceed noise levels of more than 90 dB

### Legal advice

CE and EAC compliant

\* for precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

\*\* based on inflating a 13" tyre from flat to 2.41 BAR

Application advice:  
For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.