

BATTERYstart PRO 700



Developed by and for professionals

Built for the Trade



Engine Size

Can start vehicles with up to 8.0 L petrol & up to 6.0 L diesel engines For small/medium/large cars & vans.



Lithium Phosphate battery (LiFePO₄)

Much smaller in size compared traditional Lead Acid starters, the OSRAM BATTERYstart PRO 700 is up to 75% lighter, yet still delivers high performance power.



Rapid Recharge

The Rapid Recharge function allows the clamps to remain connected to the vehicle and will recharge the OSRAM BATTERYstart PRO 700 from the vehicle alternator in around 60 seconds*

Compact Lithium Phosphate jump starter for professional Workshops

The OSRAM BATTERYstart PRO 700 is a compact lithium-phosphate battery starter (LiFePO₄) developed by and for professionals and can be optimally used in professional workshops. Developed for use in vehicles with up to 8 L petrol engine and up to 6 L diesel engine. Much smaller in size compared to traditional Lead Acid starters, the BATTERYstart PRO 700 is up to 75% lighter, yet still delivers high performance power. The Rapid Recharge function allows the clamps to remain connected to the vehicle and will recharge the starter from the vehicle alternator in around 60 seconds, if first used fully charged*. It includes intelligent safety clamps to manage power between the jump starter and vehicle, maintaining user safety during Rapid Recharge as well providing reverse polarity, short circuit and anti-spike protection. The durable and robust rubber construction makes the BATTERYstart PRO 700 optimal for use in professional workshops. It is supplied with a 220 V docking-station, which can be used to quickly recharge the BATTERYstart Pro 700.*The BATTERYstart Pro 700 must have been fully charged before the start process.



Product family datasheet

Technical data

Product description	Product information			
	Efficiency	Recommended Petrol Engine size (up to)	Recommended Diesel Engine size (up to)	USB sockets 2.1A
BATTERY start 700 ¹⁾	Professional	8 l	6 l	0

Product description	12V Power socket connection	Electrical data		Dimensions & weight	
		Cranking Amps	Peak Amps	Height	Width
BATTERY start 700 ¹⁾	n/a	650	1500	165.0 mm	170.0 mm


Product description	Length	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
		Date of Declaration	Primary Article Identifier	Candidate List Substance 1
BATTERY start 700 ¹⁾	227.0 mm	01-01-2022	4052899620506	Lead

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
BATTERY start 700 ¹⁾	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	f6e4eb05-a961-4a45-ba07-92e1c694fed2

¹⁾ Up to 8L Petrol 6L Diesel

Product family datasheet

Download Data

File	
	User instruction BATTERYstart

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.