

TYREinflate Connect 650



Download via App

The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650



Auto Stop function

Auto Stop function when pre-set pressure is reached.



Leak Detection

Including function to detect a loss of tyre pressure



OSRAMconnect

Connecting you with your car



OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation³⁾ of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and the associated information and has a function to detect a loss of tyre pressure. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes²⁾ gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product¹⁾1) For precise conditions please refer to: www.osram.com/am-guarantee2) Based on inflating a 13" tyre from flat to 2.41 BAR3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres


Product family datasheet

Technical data

| Product description | Electrical data | Dimensions & weight | | | Additional product data | Capabilities |
|--------------------------|-----------------|---------------------|---------|----------|-------------------------|--------------|
| | Nominal voltage | Length | Width | Height | Display Type | Fuse |
| TYRE inflate Connect 650 | 11.1 V | 200.0 mm | 90.0 mm | 219.0 mm | Digital | 10 A |

| Product description | Country specific categorizations | Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | |
|--------------------------|----------------------------------|--|----------------------------|----------------------------------|
| | Order reference | Date of Declaration | Primary Article Identifier | Declaration No. in SCIP database |
| TYRE inflate Connect 650 | OTIC650 | 07-03-2024 | 4052899622883 | In work |

Download Data

| File | |
|---|---|
|  | User instruction TYREinflate Connect 650 |

Safety advice

Reaches a maximum noise level of 90 db.

Legal advice

- 1) For precise conditions please refer to: www.osram.com/am-guarantee
- 2) Based on inflating a 13" tyre from flat to 2.41 BAR
- 3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Application advice:For more detailed application information and graphics please see product datasheet and the user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.