

# OPTOTRONIC Wireless Intelligent - Casambi NFC Track

Compact constant current LED driver - Dimmable



## Areas of application

- Track lights
- Shops and hospitality: retail, hotels, restaurants

# Product family benefits

- High quality of light thanks to low output ripple current
- Short housing for minimum distance between spotlights
- Versatile CASAMBI window driver due to flexible output characteristic
- Easy and fast output current setting via NFC
- High-quality dimming of 1...100 % by amplitude dimming
- SELV system

## Product family features

- Driver with integrated CASAMBI lighting control system

- Supply voltage: 220...240 V

- Line frequency: 0 Hz | 50 Hz | 60 Hz

Line voltage: 198...264 VLifetime: up to 100,000 hType of protection: IP20

# Product family datasheet

### Application advice

For more detailed application information and graphics please see product datasheet.

### Sales and Technical Support

Sales and Technical Support www.osram.com

## Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.