

# LEDDriving SLT W5W

LEDDriving interior lamps for trucks




**LED replacement lamp with a color temperature of up to 6,000 K**

Modern and intense uniform illumination



**Replaces all conventional W5W 24 V lamp bases**

Easy upgrade to LED technology with plug & play solution



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



## Suitable LED replacement for W5W

LEDDriving SLT W5W replacement lamps offer a modern and intense light with a cool white color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SLT lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference	2845DWP
Product type (off-road vs. on-road)	Off-road $\triangleq$ W5W
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications


Electrical data

Power input	0.7 W
Test voltage	28.0 V
Power input tolerance	$\pm 25\%$
Nominal wattage	0.70 W
Nominal voltage	24.0 V

Photometrical data

Color temperature	6000 K
Luminous flux	65 lm
Luminous flux tolerance	$\pm 25\%$
Light color LED	Cool white

Dimensions & weight



Product weight	1.90 g
Length	26.8 mm
Diameter	10.1 mm

Lifespan

Lifespan Tc	3000 h
Guarantee	4 years
Lifespan B3	1500 h

Additional product data

Base (standard designation)	W2.1x9.5d
-----------------------------	-----------

Capabilities

Technology	LED
------------	-----

Country specific categorizations

Order reference	2845DWP
-----------------	---------

Environmental information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	04-04-2024
Primary Article Identifier	4008321875648   4008321875990   4052899434219   4052899434233   4052899434189
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	9dde112e-87b5-4bcd-9747-1df99d8a8f5b   f6501be4-cb8f-4e3b-abb1-f5a1fdfa4baf   9d9da70e-2ccb-467f-aa31-7354af50f022   ac87ed65-a4bf-4b1b-ab5e-93e0ff336cce   0a9d8b2f-1a38-4f79-9467-b27d0c6f3b2a

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321875648	LEDiving PREMIUM SL ≙ W5W	Blister 2	135 mm x 95 mm x 13 mm	0.17 dm <sup>3</sup>	16.00 g
4008321875655	LEDiving PREMIUM SL ≙ W5W	Shipping carton box 10	71 mm x 104 mm x 146 mm	1.08 dm <sup>3</sup>	116.00 g
4062172369657	LEDiving PREMIUM SL ≙ W5W	Blister 2	135 mm x 95 mm x 13 mm	0.17 dm <sup>3</sup>	14.00 g
4062172369664	LEDiving PREMIUM SL ≙ W5W	Shipping carton box 20	140 mm x 105 mm x 146 mm	2.15 dm <sup>3</sup>	194.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures Sales Folder LEDriving replacement lamps (EN)
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

